

Informationen zum Produkt


600RE-M/600REDH-M



Füllvolumen:	Maße:	Höhe o.D.:	Gewicht Becher (ohne Bügel), Deckel (+/-3%)	IML-Druck Becher	IML-Druck Deckel	Weiteres:
600ml	135x103mm	83mm	36g / 10,5g	nein	ja	Siehe Spez.
<ul style="list-style-type: none"> • PP-Spritzgussbecher mit Originalitätsverschluss (Zertifikat Lebensmittelsicherheit) • Standardausführung: klar mit klarem Deckel (Einfärbung in Standard-/Sonderfarben möglich) 						
Menge je Palette Schalen:	in 16 Boxen gepackt je:	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Einweg-Palette	Pal-Höhe	Weiteres:
6.400 St.	400 St.	580x400x500mm 650g	120g	1200x800x150mm 12kg	2,20m	Siehe Spez.
Menge je Palette Deckel:	in 28 Boxen gepackt je:	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Einweg-Palette	Pal-Höhe	Weiteres:
22.400 St.	800 St.	520x320x270mm 360g	120g	1200x800x150mm 12kg	2,20m	Siehe Spez.

Technical specification:

Tolerance: Weight/Volume +/- 5,0% Domensions +/- 0,5 mm



	Container	Lid
Volume to the edge	600ml.	
Material/weight	PP /36 g	PP/ 10,5 g
Top dimension D-D1	135x103mm	D1 132x99mm
Bottom dimension Š-Š1	115x81mm	
Height with lid V	V 83,7 mm	8,5 mm
Number in 1 ct	400	800
Number of ct on 1 palette	16	22400

Other characteristic

Uses:

containers with lids are intended for direct contact with watery, acidic, fat food products, which temperature is room and lower.

Hot filling:

packaging is suitable for contact with the hot filling (85°C-95°C) and short-term use in the microwave. Packaging must be tested by the customer with the actual product before to written approval for use at hot temperatures.

Cold temperatures:

packaging made from the special cold-resistant material can be used at temperatures -20°C. It is produced according to customer requirements. Packaging must be tested by the customer with the actual product before to written approval for use at low temperatures.

Storage:

suitable storage includes protection of direct sun light, rain, very high temperatures over a long period. Packaging must be not more than 2,4m in height and at least 1m away from heat source.

Recommended period of storage – 12 months after delivery to suitable storage.