

Informationen zum Produkt



1180DH

Weitere Füllvolumen Ø 133mm:

500ml
1.060ml
1.180ml



Füllvolumen:	Ø:	Höhe m.D.:	Gewicht Becher, Deckel (+/-3%)	IML-Druck Becher	IML-Druck Deckel	Weiteres:
1.186ml	133mm	128,6mm	40,42g / 9,02g	ja	ja	Siehe Spez.
<ul style="list-style-type: none"> • PP-Spritzgussbecher mit Originalitätsverschluss (BRC-Zertifikat Lebensmittelsicherheit) • Standardausführung: klar mit klarem Deckel (Einfärbung in Standardfarben möglich) • Fertigung in Tiefkühlqualität zur Erhöhung der Schlagfähigkeit auf Anfrage (Eisindustrie) 						
Menge je Palette:	in 20 Kombiboxen paarig gep.	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Palette	Paletten-Höhe	Weiteres:
3.400 St.	170 St.	592x392x400mm 720g	28g	1200x800x150mm 23kg	Inkl. Pal. 2,20m	Siehe Spez.

Standardfarben zur Einfärbung



schwarz



rot



braun



weiss



orange



gelb



grün



blau



dunkelblau

Technical Data Sheet

Container 1180 ml Ø131 H, lid H

1. Dimensions	Shape:	Round	
	Volume under lid:	1186	ml
	External diameter top (with lid):	132,9	mm
	External diameter bottom:	106	mm
	Height (with lid):	128,6	mm
2. Closure system	Closure type:	Snap-On	
	Protective collar:	Yes	
	Tamper evident:	Yes	
	Lid type options:	Standard lid	
3. Weight*	Container:	37,88	g
	Lid:	9,02	g
	Handle:	2,54	g
	*the weight can have +/-3 % error		
4. Handle	Handle available:	Yes	
5. Raw material	Raw material:	PP	
	Masterbatch colours:	Standard colours or colours coordinated according to customer's presented colour pallet or sample.	
	Approvals:	All raw materials and masterbatches used in the production process have the appropriate food contact approvals.	
6. Decoration	IML decoration (container):	Yes	
	IML decoration (lid):	Yes	
7. Other characteristic	Uses:	Containers with lids are intended for direct contact with watery, acidic, fat food products, which temperature is room and lower.	
	Hot filling:	Packaging is suitable for contact with the hot filling (85 ° C - 95 ° C) and short-term use in the microwave. Packaging must be tested by the customer with the actual product before approval for use at hot temperatures.	
	Cold temperatures:	Package made from the special cold-resistant material can be used at temperatures below -20 °C . It is produced according to customer requirements. Packaging must be tested by the customer with the actual product before approval for use at low temperatures.	
	Storage:	Suitable storage include protection of direct sun light, rain, very high temperatures over a long period. Package must be not more than 2.4 m in height and at least 1 m away from the heat source. Recommended period of storage - 12 months after delivery to suitable storage.	
8. Packing	Standard		
	Containers per plastic bag	500	pcs.
	Lids per carton box	1000	pcs.
	Plastic bags per pallet	8	pcs.
	Carton boxes per pallet	4	pcs.
	Containers per pallet	4000	pcs.
	Lids per pallet	4000	pcs.
	Height including pallet	2,45	m
	Containers and lids packed together per carton box	170	pcs.
	Carton boxes per pallet	20	pcs.
	Containers and lids packed together per pallet	3400	pcs.
	Height including pallet	2,25	m
	Optional		
	Carton boxes per pallet	24	pcs.
	Containers and lids packed together per pallet	4080	pcs.
Height including pallet	2,65	m	

