

## Informationen zum Produkt

## 2300DH



Füllvolumen:	Ø:	Höhe m.D.:	Gewicht Becher, Deckel (+/-3%)	IML-Druck Becher	IML- Druck Deckel	Weiteres:
2300ml	168mm	154,4mm	71,01g / 17,81g	nein	nein	Siehe Spez.
<ul style="list-style-type: none"> <li>• PP-Spritzgussbecher mit Originalitätsverschluss (BRC-Zertifikat Lebensmittelsicherheit)</li> <li>• Standardausführung: klar mit klarem Deckel (Einfärbung in Standardfarben möglich)</li> <li>• Fertigung in Tiefkühlqualität zur Erhöhung der Schlagfähigkeit auf Anfrage (Eisindustrie)</li> </ul>						
Menge je Palette:	in 20 Kombiboxen paarig gep.	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Palette	Paletten- Höhe	Weiteres:
1.680 St.	84 St.	592x392x400mm 720g	28g	1200x800x150mm 23kg	Inkl. Pal. 2,20m	Siehe Spez.

## Standardfarben zur Einfärbung



**schwarz**



**rot**



**braun**



**weiss**



**orange**



**gelb**



**grün**



**blau**



**dunkelblau**

## Technical Data Sheet

### Container 2000 ml Ø168 OL, lid OL

<b>1. Dimensions</b>	Shape:	Round	
	Volume under lid:	2300	ml
	External diameter top (with lid):	167,9	mm
	External diameter bottom:	134,8	mm
	Height (with lid):	154,4	mm
<b>2. Closure system</b>	Closure type:	Snap-On	
	Protective collar:	Yes	
	Tamper evident:	Yes	
	Lid type options:	Standard lid	
<b>3. Weight*</b>	Container:	67,52	g
	Lid:	17,81	g
	Handle:	3,49	g
	*the weight can have +/-3 % error		
<b>4. Handle</b>	Handle available:	Yes	
<b>5. Raw material</b>	Raw material:	PP	
	Masterbatch colours:	Standard colours or colours coordinated according to customer's presented colour pallet or sample.	
	Approvals:	All raw materials and masterbatches used in the production process have the appropriate food contact approvals.	
<b>6. Decoration</b>	IML decoration (container):	No	
	IML decoration (lid):	No	
<b>7. Other characteristic</b>	Uses:	Containers with lids are intended for direct contact with watery, acidic, fat food products, which temperature is room and lower.	
	Hot filling:	Packaging is suitable for contact with the hot filling (85 ° C - 95 ° C) and short-term use in the microwave. Packaging must be tested by the customer with the actual product before approval for use at hot temperatures.	
	Cold temperatures:	Package made from the special cold-resistant material can be used at temperatures below -20 °C . It is produced according to customer requirements. Packaging must be tested by the customer with the actual product before approval for use at low temperatures.	
	Storage:	Suitable storage include protection of direct sun light, rain, very high temperatures over a long period. Package must be not more than 2.4 m in height and at least 1 m away from the heat source. Recommended period of storage - 12 months after delivery to suitable storage.	
<b>8. Packing</b>	<b>Standard</b>		
	Containers per plastic bag	300	pcs.
	Lids per carton box	600	pcs.
	Plastic bags per pallet	6	pcs.
	Carton boxes per pallet	3	pcs.
	Containers per pallet	1800	pcs.
	Lids per pallet	1800	pcs.
	Height including pallet	2,4	m
	Containers and lids packed together per carton box	84	pcs.
	Carton boxes per pallet	20	pcs.
	Containers and lids packed together per pallet	1680	pcs.
	Height including pallet	2,2	m
	<b>Optional</b>		
	Carton boxes per pallet	24	pcs.
	Containers and lids packed together per pallet	2016	pcs.
Height including pallet	2,6	m	

